

**IN THE CLAIMS:**

Please amend the claims as set forth below:

1. (Currently Amended) A method comprising:

detecting that an application in a first node is to failover, wherein the first node is included in a cluster being used to execute the application;

adding a second node to the cluster responsive to the detecting;

provisioning ~~a second~~ the second node to execute the application responsive to the detecting; and

failing the application over from the first node to the second node.

2. (Original) The method as recited in claim 1 wherein the provisioning comprises activating one or more resources used by the application on the second node.
3. (Original) The method as recited in claim 1 wherein the provisioning comprises installing one or more resources used by the application on the second node.
4. (Original) The method as recited in claim 1 wherein the second node has multiple boot capability, and wherein the provisioning comprises rebooting the second node from a partition that comprises one or more resources used by the application.
5. (Original) The method as recited in claim 1 further comprising selecting the second node from a plurality of nodes.
6. (Original) The method as recited in claim 5 wherein the second node is executing a different application when selected.

7. (Original) The method as recited in claim 5 wherein the selecting comprises verifying that the second node includes hardware that is sufficient to execute the application.

8. (Original) The method as recited in claim 1 further comprising adding the first node to the plurality of nodes to be selectable for provisioning.

9. (Cancelled)

10. (Original) The method as recited in claim 1 wherein the detecting comprises detecting that the performance of the application executing on the first node is less than a threshold performance level.

11. (Original) The method as recited in claim 10 wherein the performance is less than the threshold performance level for at least a predefined time interval.

12. (Original) The method as recited in claim 10 wherein the detecting comprises alternatively detecting a failure in a service group including the application.

13. (Original) The method as recited in claim 1 wherein the detecting comprises detecting a failure in a service group including the application.

14. (Original) The method as recited in claim 1 further comprising detecting a lack of success in the failing over.

15. (Original) The method as recited in claim 14 further comprising:

provisioning a third node to execute the application responsive to detecting the lack of success; and

failing the application over from the second node to the third node.

16. (Currently Amended) ~~The method as recited in claim 14~~ A method comprising:

detecting that an application in a first node is to failover;

provisioning a second node to execute the application responsive to the detecting;

attempting to failover the application from the first node to the second node;

detecting a lack of success in the failover, wherein the lack of success is due to a lack of an eligible node; ~~and, and wherein,~~

permitting the application to execute on the first node responsive to the lack of the eligible node if ~~detecting that the attempt to application~~ is to failover is due to a performance of the application on the first node being less than a threshold performance level, ~~the method further comprises permitting the application to execute on the first node.~~

17. (Currently Amended) The method as recited in claim 16 ~~claim 14 wherein the lack of success is due to a lack of an eligible node, and~~ wherein, if ~~detecting that the application is the attempt~~ to failover is due to a failure in a service group including the application, the method further comprises notifying an administrator.

18. (Original) The method as recited in claim 1 further comprising:

determining that a performance level on the second node is less than a threshold;

provisioning a third node to execute the application responsive to the determining;  
and

failing the application over from the second node to the third node.

19. (Currently Amended) A computer accessible medium encoded with instructions that, when executed:

detect that an application in a first node is to failover, wherein the first node is included in a cluster being used to execute the application;

add a second node to the cluster responsive to detecting that the application is to failover;

~~provision a second~~ the second node to execute the application responsive to detecting that the application is to failover; and

failover the application from the first node to the second node.

20. (Original) The computer accessible medium as recited in claim 19 wherein the instructions which, when executed, provision the second node comprise instructions which, when executed, activate one or more resources used by the application on the second node.

21. (Original) The computer accessible medium as recited in claim 19 wherein the instructions which, when executed, provision the second node comprise instructions which, when executed, install one or more resources used by the application on the second node.

22. (Original) The computer accessible medium as recited in claim 19 wherein the second node has multiple boot capability, and wherein the instructions which, when executed, provision the second node comprise instructions which, when executed, reboot the second node from a partition that comprises one or more resources used by the application.

23. (Original) The computer accessible medium as recited in claim 19 wherein the

instructions, when executed, select the second node from a plurality of nodes.

24. (Original) The computer accessible medium as recited in claim 23 wherein the instructions which, when executed, select the second node comprise instructions which, when executed, verify that the second node includes hardware that is sufficient to execute the application.

25. (Original) The computer accessible medium as recited in claim 23 wherein the instructions, when executed, add the first node to the plurality of nodes to be selectable for provisioning.

26. (Cancelled)

27. (Original) The computer accessible medium as recited in claim 19 wherein the instructions which, when executed, detect that the application is to failover comprise instructions which, when executed, detect that the performance of the application executing on the first node is less than a threshold performance level.

28. (Original) The computer accessible medium as recited in claim 27 wherein the performance is less than the threshold performance level for at least a predefined time interval.

29. (Original) The computer accessible medium as recited in claim 27 wherein the instructions which, when executed, detect that the application is to failover comprise instruction which, when executed, alternatively detect a failure in a service group including the application.

30. (Original) The computer accessible medium as recited in claim 19 wherein the instructions which, when executed, detect that the application is to failover comprise instruction which, when executed, detect a failure in a service group including the application.

31. (Currently Amended) A system comprising a plurality of nodes, wherein a first node of the plurality of nodes is configured to monitor performance of an application executing on a second node of the plurality of nodes during use, and wherein, in response to a detection that the application is to failover from the first node, a third node is configured to be provisioned to execute the application, wherein the second node is included in a cluster being used to execute the application, and wherein the third node is added to the cluster responsive to the detection that the application is to failover from the second node during use, and wherein the application is failed over to the third node during use.

32. (Original) The system as recited in claim 31 wherein provisioning the third node comprises activating one or more resources used by the application on the second node.

33. (Original) The system as recited in claim 31 wherein provisioning the third node comprises installing one or more resources used by the application on the third node.

34. (Original) The system as recited in claim 31 wherein the third node has multiple boot capability, and wherein provisioning the third node comprises rebooting the third node from a partition that comprises one or more resources used by the application.

35. (Cancelled)

36. (Original) The system as recited in claim 31 wherein the first node is configured to detect that the performance of the application executing on the second node is less than a threshold performance level.

37. (Original) The system as recited in claim 36 wherein the performance is less than the threshold performance level for at least a predefined time interval.

38. (Original) The system as recited in claim 31 wherein the second node is configured to detect a failure in a service group including the application, and wherein the application is to failover from the second node if the second node detects the failure.

39. (New) The method as recited in claim 1 further comprising removing the first node from the cluster responsive to successfully failing over the application to the second node.

40. (New) The computer accessible medium as recited in claim 19 wherein the instructions, when executed, remove the first node from the cluster responsive to successfully failing over the application to the second node.

41. (New) The system as recited in claim 31 wherein the second node is removed from the cluster responsive to a successful failover to the third node.